

Amendments to the Claims:

1) Please cancel claims 15 and 18 without prejudice or disclaimer of the subject matter thereof.

Listing of Claims:

Claim 1 (Previously presented): A press-fitted hub system comprising:

a base body formed as a shaft and having at least one region of material aggregate adapted to have a diameter larger than the diameter of the shaft; and

at least one hub having a hub opening in a front face for pressing onto the base body, whereby the hub opening has an insertion area tapering in a press-on direction, a first cylindrical section arranged as viewed between the front face and insertion area, and a second cylindrical section arranged on the opposite side of the insertion area with reference to the first cylindrical section;

wherein the length of the first cylindrical section is about 2 % to 30 % of the entire length of the hub;

wherein the diameter of the first cylindrical section of the hub opening is at least the same size as the largest diameter of the base body, on which the hub is to be pressed;

wherein the insertion area is tapered in a press-on direction, and the diameter of the first cylindrical section greater than the diameter of the second cylindrical section.

Claim 2 (Previously presented): The press-fitted hub system according to claim 1, wherein the material aggregate being adapted to deform when the insertion area and the second cylindrical section is pressed thereon, thereby producing a friction connection between the hub and the base body.

Claim 3 (Previously presented): The press-fitted hub system according to claim 2, wherein the material aggregate is in the form selected from the group consisting of coils and bars, and wherein the material aggregate can extend either in the circumferential direction of the base body or parallel to the longitudinal axis of the hub.

Claim 4 (Previously presented): The press-fitted hub system according to claim 1, characterized in that the tapered insertion area has a curve profile, whereby the curve profile is formed from circular segments with different radii placed on one another, and whereby the radii of the circular segments are smaller toward the first cylindrical section.

Claim 5 (Previously presented): The press-fitted hub system according to claim 1, characterized in that the insertion region has a curve profile, whereby the curve profile is formed by an arch, which discontinuously connects to the first cylindrical section and opens discontinuously or continuously into the second cylindrical section.

Claim 6 (Previously presented): The press-fitted hub system according to claim 1, characterized in that the insertion area is formed by a truncated cone, which connects the first cylindrical and second cylindrical sections by means of transition edges.

Claim 7 (Previously presented): The press-fitted hub system according to claim 1, characterized in that the insertion area is divided into two subsections and both subsections of the insertion area are formed in the shape of a truncated cone along the longitudinal axis each having a cone angle different from the other, and that the cone angle of a first subsection arranged toward the first cylindrical section is greater than the cone angle of a second subsection arranged toward the second cylindrical section.

Claim 8 (Previously presented): The press-fitted hub system according to claim 7, characterized in that the diameter of the second cylindrical section is at least the same size as the diameter of the base body.

Claim 9 (Cancelled).

Claim 10 (Previously presented): The press-fitted hub system according to claim 8, characterized in that the length of the second cylindrical section is about 2 % to 30 % of the entire length of the hub.

Claim 11 (Previously presented): The press-fitted hub system according to claim 10, characterized in that the length of the insertion area includes 40 % to 96 % of the entire length of the hub.

Claim 12 (Previously presented): The press-fitted hub system according to claim 11, characterized in that the ratio of length of the first subsection to the second subsection lies between 0.1 and 10.

Claim 13 (Previously presented): The press-fitted hub system according to claim 12, characterized in that the first conical angle is about 16° to 30°.

Claim 14 (Previously presented): The press-fitted hub system according to claim 13, characterized in that the second conical angle is about 1° to 15°.

Claim 15 (Cancelled).

Claim 16 (Previously presented): The press-fitted hub system according to claim 14 further comprising at least one cam.

Claim 17 (Previously presented): The press-fitted hub system according to claim 16 further comprising a camshaft including the cam and hub, wherein the base body is a shaft on which the cam is pressed thereon.

Claim 18 (Cancelled).

Claim 19 (Previously presented): A press-fitted hub system comprising:

- a base body formed as a shaft and having at least one region of material aggregate adapted to have a diameter larger than the diameter of shaft;

- a camshaft having at least one cam, wherein the cam having a hub opening for receiving the base body, wherein the hub opening has an insertion area tapered in the press-on direction, characterized in that, viewed in the press-on direction, a first cylindrical section is arranged between the front face and the insertion region;

- wherein the length of the first cylindrical section is about 2 % to 30 % of the entire length of the hub;

- wherein the hub further comprising a second cylindrical section, the second cylindrical section with reference to the first cylindrical section is arranged on the opposite side of the insertion area, and

- wherein the material aggregate being adapted to deform when the insertion area and the second cylindrical section is pressed thereon;

- wherein the insertion area is tapered in a press-on direction, and the diameter of the first cylindrical section greater than the diameter of the second cylindrical section.